

ROTAX® ENGINE	600 ACE	600 EFI
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, two-stroke
Cylinders	2	
Displacement	600 cc	599.4 cc
Bore	74 mm	72.3 mm
Stroke	69.7 mm	73 mm
Maximum engine speed	7250 RPM	7500 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	
Oil tank capacity (2-stroke)	3.4 liters	

Viper Red / Black	

### DIMENSIONS

COLOUR

3240 mm	
1200 mm	
1500 mm	
996 mm	
500 mm	
3923 mm	
ile height 38 mm	

# POWERTRAIN

Drive clutch type	eDrive II	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

# SUSPENSION

Front suspension LFS+		
Front shock	KYB 36	
Rear suspension	EasyRide+	
Center shock	KYB 36	
Rear shock	KYB 36	

## **DRY WEIGHT**

Dry weight	247 kg	241 kg
------------	--------	--------

#### **FEATURES**

Frame	Radien-X	Heated throttle lever	Standard
Skis	Blade DS+	Heated grips	Standard
Seating	Modular, 1-up	Gauge	4.5" digital display
Handlebar	U-type steel with hooks	Windshield	Extra high with side deflectors
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric and manual (EFI) Electric (ACE)	USB power outlet	Yes, in front compartment
		Air radiator with fan	Yes
Reverse	RER (EFI) Electromechanical (ACE)	LinQ attachment	Multi-LinQ plate

