## 2025

**EXPEDITION° LE** 

A crossover sport-utility vehicle capable of off-trail exploration, on-trail cruises and enjoyable work days.



## // PACKAGE HIGHLIGHTS

- Two Rotax® engines available: 900 ACE Turbo, 900 ACE
- Available with 20 in. or 24 in. track options
- Multi-LinQ plate with 125 lb / 56.7 kg cargo capacity
- RAS™ X crossover front suspension with 39 in. ski stance
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- · Air radiator with fan
- Deep snow running boards with large openings
- Removable passenger seat with heated grips
- High passenger backrest
- Hitch
- · High capacity battery
- pDrive™ clutch

- Easy Shift transmission (H-L-N) with electro-mechanical reverse
- Ultra-high windshield with side deflectors
- Pivoting mirrors
- Pilot 7.4 skis
- Heated driver's visor power outlet
- · Low handlebar strap

ROTAX ENGINE	900 ACE TURBO	900 ACE
Engine details	Liquid-cooled,	Liquid-cooled,
	four-stroke D.O.H.C.,	four-stroke D.O.H.C.,
	dry sump,	dry sump
	turbocharged	
Horsepower*	130	95
Cylinders -	3	3
Displacement	899 cc	899 cc
Bore - Stroke (mm)	73 x 69.7	73 x 69.7
Fuel System	EFI	EFI
Fuel type – Octane	Regular unleaded - 95	Regular unleaded - 95
Fuel tank (L/US gal)	42 / 11.1	42 / 11.1
Oil tank capacity (L/qt)	3.3 / 3.5	3.3 / 3.5
POWERTRAIN		
Drive clutch	pDrive™	pDrive™
Driven clutch	QRS Vent	QRS
Drive sprocket pitch (mm/in.)	73 / 2.86	73 / 2.86
DRY WEIGHT		
Dry weight 20 in. track (kg)	303.5	291.7
Dry weight 24 in. track (kg)	313	301.2

DIMENSIONS	
Vehicle overall length (mm/in.)	3,256 / 128.2
Vehicle overall width (mm/in.)	1,200 to 1,240 / 47.7 to 48.8
Vehicle overall height (mm/in.)	1,513 / 59.6
Ski stance (mm/in.)	1,000 / 39 (adjustable)
Available tracks (in.)	Silent Cobra WT: 154 x 20 x 1.5

SUSPENSION		
Front suspension	RAS™ X	
Front shock	KYB 36	
Front suspension travel (mm/in.)	220 / 8.7	
Rear suspension	SC™-5U	
Center shock	KYB 36	
Rear shock	KYB 36	

239 / 9.4

COLOR	
Black Black	
Catalyst Grey	
FEATURES	
Platform	REV® Gen4
Headlights	Halogen
Skis	Pilot™ 7.4
Seating	WideTrack 2-up
Handlebar	Standard with J-hooks / Grab handle
Riser block height (mm/in.)	145 / 5.7
Starter	Electric
Reverse	Electro-mechanic
Air radiator	Fan
Brake system	Brembo
Heated throttle lever/grips	Standard (driver and passenger)
Gauge type	4.5 in. digital
Windshield	Ultra-high with mirrors
Runner (in.) – Carbide (in.)	3/8 square / 4
Bumpers (front/rear)	Heavy Duty / Hitch





Rear suspension travel (mm/in.)