2025 FREERIDE[™]

Extreme capacity deep snow sled built to live large, live free and go big. The Freeride is stable and predictable at higher speed in variable snow conditions, including bigger bumps.

// WHAT'S NEW

- Precision rack steering system
- 10.25 in. touchscreen display with BRP Connect and built-in GPS



FREERIDE 154 850 E-TEC TURBO R SHOWN

// PACKAGE HIGHLIGHTS

- REV Gen5 platform
- Rotax® 850 E-TEC® Turbo R and 850 E-TEC engines available
- Premium LED headlights
- Short tunnel with lightweight snowflap
- tMotion XT rear suspension with rigid rear arm
- Reinforced rails
- E-TEC® SHOT™ starter standard

- Narrow extruded profile running boards with extra-large openings
- Sway bar quick-disconnect
- oway bar quion alocomilos
- Low handlebar strap
- PowderMax X-Light 3 in. with FlexEdge
- Compact deep snow seat
- Belt-monitoring system
- Narrow bodywork

PowderMax[†]:

146 x 15 x 2.5 PowderMax[†] X-Light: 154 X 15 X 3.0

- · Adjustable brake lever
- KYB Pro 40 EA-3 front shocks with lightweight springs
- Pilot DS 4 skis
- 15-in. full-rod track
- Short riser block (120 mm / 4.7 in.)
- RAS™ 3 front suspension with 36 in. ski stance

| ROTAX ENGINE | 850 E-TEC TURBO R | 850 E-TEC |
|---------------------------------|---|--|
| Engine details | Liquid-cooled, two-stroke, turbocharged, eRAVE™ | Liquid-cooled, two-stroke, eRAVE™ |
| Horsepower* | 180 up to 8,000 ft. | 165 |
| Cylinders - Displacement | 2 - 849 cc | 2 - 849 cc |
| Bore - Stroke (mm) | 82 x 80.4 | 82 x 80.4 |
| Fuel System | E-TEC® direct injection with additional booster injectors | E-TEC® direct injection with additional booster injectors |
| Fuel type – Octane | Regular unleaded - 95 | Regular unleaded - 95 |
| Fuel tank (L/US gal) | 36 / 9.5 | 36 / 9.5 |
| Oil tank capacity (L/qt) | 3.4 / 3.6 | 3.4 / 3.6 |
| POWERTRAIN | | |
| Drive clutch Driven clutch | pDrive™ with clickers QRS Vent Plus | |
| Drive sprocket pitch (mm/in.) | 73 / 2.86 (146 - 154 x 2.5 in.) 89 / 3.5 (154 x 3.0 - 165 in.) | |
| DRY WEIGHT | | |
| Dry weight (kg) | 212.3 (146 in.) 210 (154 in.) | 203.2 (146 in.) 201.4 (154 in.) |
| DIMENSIONS | | |
| Vehicle overall length (mm/in.) | 3,058 / 120.4 [146 in.] 3,188 / 125.5 [154 in.] | |
| Vehicle overall width (mm/in.) | 1,073 / 42.2 (adjustable) | |
| Vehicle overall height (mm/in.) | 1,395 / 54.9 | |
| Ski stance (mm/in.) | 930 / 36 (adjustable) | |
| | | |

| Flare Yellow (painted) | | |
|----------------------------------|--|--|
| SUSPENSION | | |
| Front suspension | RAS 3 | |
| Front shock | KYB Pro 40 EA-3 w/ lightweight springs | |
| Front suspension travel (mm/in.) | 215/8.5 | |
| Rear suspension | tMotion XT | |
| Center shock | KYB Pro 40 EA-3 w/ lightweight spring | |
| Rear shock | KYB Pro 40 EA-3 | |
| Rear suspension travel (mm/in.) | 264/10.4 | |
| FEATURES | | |
| Platform | REV® Gen5 | |
| Headlights | Premium high-performance LED | |
| Skis | Pilot™ DS 4 | |
| Seating | Deep snow compact | |
| Handlebar | Tapered with J-hooks / Grab handle | |
| Riser block height (mm/in.) | 120 / 4.7 | |
| Starter | SHOT | |
| Reverse | RER™ | |
| Brake system | Brembo with adjustable lever | |
| Heated throttle lever/grips | Standard | |
| Gauge type | 4.5 in. digital | |
| | 10.25 in. touchscreen (opt.) | |
| Windshield | Optional | |
| Runner (in.) - Carbide (in.) | 3/8 square / 4 | |
| Bumpers (front/rear) | Std / Std | |



Available tracks (in.)

(Length x width x profile)

